

















TDS- Parameters default FS390

Datasheet Automatic mode:

																		
		Bottom (valori per PAR1=6)	Up cycle (valori per PAR1=6)	Top (valori per PAR1=6)	Down cycle (valori per PAR1=6)	Bottom (valori per PAR1=4)	Up cycle (valori per PAR1=4)	Top (valori per PAR1=4)	Down cycle (valori per PAR1=4)	Up cycle	Down cycle	Bottom	Up cycle	Top	Down cycle	Bottom	Top	
	enable/disable	100-400	100-400	100-400	100-400	1-9	1-9	1-9	1-9	1-9	1-9	1-9	1-9	1-9	1-9	0-9	0-9	5-50, step 5
P1																		
P2																		
P3																		
P4																		
P5																		
P6																		
P7																		
P8																		
P9																		
P10																		
P11																		
P12																		
P13																		
P14																		
P15																		
P16																		
P17																		
P18																		
P19																		
P20																		
P21																		
P22																		
P23																		
P24																		
P25																		
P26																		
P27																		
P28																		
P29																		
P30																		

TDS- Parameters default FS390

Datasheet Automatic mode:

										
	1-9, step 1	1-40, step 1	5-300, step 5	5-180, step 5	1-9, step 1	0-60, step 5	5-40, step 5	15-200, step 5	1-9, step 1	15-200, step 5
P1										
P2										
P3										
P4										
P5										
P6										
P7										
P8										
P9										
P10										
P11										
P12										
P13										
P14										
P15										
P16										
P17										
P18										
P19										
P20										
P21										
P22										
P23										
P24										
P25										
P26										
P27										
P28										
P29										
P30										

TDS- Parameters default FS390

Datasheet Manual mode:

TABELLA VALORI DI DEFAULT FUNZIONAMENTO MANUALE FS390			
			
1-9	1-9	100-400%, step 10	1-9
7	5	200	6