

FROMM Stretch Wrapping Division TDS_16.8216.V01.02 Page: 1/1 TECHNICAL DATA SE

TECHNICAL DATA SHEET

FROMM Loading ramps for FS machines

Art. Nr:	16.8216 Ø1650mm FS2xx / FS4xx 16.8218 Ø1800mm FS2xx / FS4xx 16.8221 Ø2200mm FS2xx / FS4xx
Advantages for the end-user:	 Length 1830mm less inclination; 2 inclinations of 4 degrees to make loading more easy; Specially used for longer electric trucks; Max load capacity 2000kg.
Measurements (I x w x h):	Length 1826mm Width 1200mm Height 74mm Diameter Ø1650mm or Ø1800mm or Ø2200mm
Weight	102kg
Construction:	Solid construction in 5mm steel. With 4 lengthwise positioned profiles and 3 profiles in the width. (Fig.3) Guaranteed long life time, quality according FROMM design.
	At the left and right side of the ramp we installed two brackets, in order to stabilize the ramp in a horizontal way. (Fig.4)
	At the front side you can connect the ramp to the machine. (Fig.2) Thru the hand grips, at the left and right side of the ramp you will find two additional bolts with which you can align the ramp in a perfect way in front of the machine. (Fig.4)
<	1826
	Ø1650mm Ø1800mm Ø2200mm



FROMM Stretch Wrapping Division TDS_16.8216.V01.02 Page: 2/2

TECHNICAL DATA SHEET

Specifications: Colour YELLOW RAL1021

Treatment:

Any slip powder paint.

Application:

Loading of pallets / trays / special products.



Figure 1



Figure 2



FROMM Stretch Wrapping Division TDS_16.8216.V01.02 Page: 3/3 **TECHNICAL DATA SHEET**







Figure 3

Figure 4

For further information please contact Ed Pennings, FROMM Stretch Wrapping Division. We sincerely hope that this information is of interest. We assure professional handling and execution of your order in advance and would be happy to assist with further information, if needed.

Best Regards, **FROMM** Packagings Systems





🖀 0039 045 624515 / 334 644 2024